



# HITEX INSULATION (NINGBO) CO., LTD

Room2004,2<sup>nd</sup> Block, Shangdong Business Centre, Ningbo,315041

Tel:+86-574-27898220,Fax:+86-574-27898230

## مشخصات فنی پارچه فایبر گلاس فویلدار ضخامت 0.8 میلی متر

1	CHARACTERISITIC		ALCTX650	
2	WEAVE		PLAIN	
3	YARN (TEX)	WARP WEFT	ET9 430 Tex ET9 430 Tex	ETG 430 Tex ETG 430 Tex
4	WIDTH		101.6cm 121.9cm 152.4cm	40 inch 48 inch 60 inch
5	THICKNESS		0.8±0.08mm	0.03±0.003 inch
6	COAT THICKNESS		Aluminum foil	
7	COAT THICKNESS		0. 18mm	0.007 inch
8	WEIGHT		600±60g/m <sup>2</sup>	17.7±1 OZ/YD <sup>2</sup>
9	THREAD COUNT	WARP WEFT	8±0.8 per cm 5.7±0.6 per cm	20.3±2 per inch 14.5±1.5 per inch
10	TENSILE STRENGTH MIN	WARP WEFT	1750 N/5cm 1250 N/5cm	194 lbs/inch 138 lbs/inch
11	L.O.I %		< 1.0%	
12	SERVICE TEMPERATURE		550°C	

All information data quoted are based on our extensive tests and years of experience, however, they can only serve as guide value. Failure to select proper sealing products could result in properly damage and/or serious injury. Specifications are subject to change without notice.