



HITEX INSULATION (NINGBO) CO., LTD

Room2004,2nd Block, Shangdong Business Centre, Ningbo,315043

Tel:+86-574-27898220,Fax:+86-574-27898230

مشخصات فنی پارچه روکش دار یک طرف سیلیکون طوسی

| | | | | |
|-------------------|---|-------------------------|--------------------------------|-----------|
| Name | SILICON SINGLE COATED GLASS FABRIC | Style | SILICONFA3732E-80G-SG-1-5 0 | |
| Date | 2013-11-01 | Test date | 2013-11-05 | |
| Test Index & Item | | | | |
| Sril | Item | Standard | Actual | Result |
| 1 | Tensile Strength(N) Warp X Weft 50mm/N | 2000 X 1700 | 2100 X 1800 | Qualified |
| 2 | Thickness | 0.45±0.05 mm | 0.45 | Qualified |
| 3 | Width | 1000 mm | 1010mm | Qualified |
| 4 | Weight of Coating | 80g/m ² | 80 | Qualified |
| 5 | Color | Silver grey | - | Qualified |
| 6 | Compressive strength | 17.6kgf/cm ² | 17.7kgf/cm ² | Qualified |
| 7 | Temperature resistance | 260°C | 280°C | Qualified |
| 8 | Extinguish Time | 3s | 1s | Qualified |
| 9 | Standard | JC/T171.1-2005 | | |

All information data quoted are based on our extensive tests and years of experience, however, they can only serve as guide value. Failure to select proper sealing products could result in properly damage and/or serious injury. Specifications are subject to change without notice.