



HITEX INSULATION (NINGBO) CO., LTD

Room2004,2nd Block, Shangdong Business Centre, Ningbo,315043

Tel:+86-574-27898220,Fax:+86-574-27898230

مشخصات فنی پارچه فایبر سرامیک سیم دار ضخامت 3 میلی متر

Name	Ceramic Fiber Cloth	Style	TCR2800S-3-1-30	
Date	2012-4-15	Test Date	2012-4-20	
Test Index & Item				
Srial	Item	Standard	Actual	Result
1	Ave. Weight (gr/m ²)	1500±150	1500	Qualified
2	Moisture content	≤2.5%	1.5%	Qualified
3	loss on Ignition	≤18%	17.8	Qualified
4	Tensile Strength(N) Warp X Weft 50mm/N	≥ 1000X550	1100X600	Qualified
5	Max. Temperature	1260°C	1260	Qualified
6	Working temperature	1100°C	1100	Qualified
7	Thermal Conductivity (538°C) w/m.k	0.130	0.130	Qualified
8	Chemical composition			
	Al ₂ O ₃	45~48%	46.12%	合格 Qualified
	Fe ₂ O ₃	0.7~1.2%	0.8%	
SiO ₂	50~52%	51.10%		
Standard GB/T 3303-2006				

All information data quoted are based on our extensive tests and years of experience, however, they can only serve as guide value. Failure to select proper sealing products could result in properly damage and/or serious injury. Specifications are subject to change without notice.